



# ÖZKAN<sup>®</sup> TARIM MAKİNE

## B3-PLUS PUMPKIN HARVESTER MACHINE


### KHM B3 PLUS



PRODUCT CODE	KHM-B3-PLUS	SHAFT SPEED / P.T.O	540/1500 S / MIN
LENGTH	5200 MM	TRACTOR CONNECTION	MECHANICAL
TRANSPORT WIDTH	2600 MM	SEED TANK DISCHARGE	AUGER
TOTAL WORKING WIDTH	4000 MM	AUGER DISCHARGE HEIGHT	4000 MM
HEIGHT	2900 MM	CONTROL METHOD	TRACTOR
WEIGHT	3800 KG	SIEVE (BOLTED)	VARIABLE
LOADED WEIGHT	6600 KG	WHEELS	500/50/17
WORKING ROW WIDTH	1350 MM	MAXIMUM WORKING SPEED	8 KM / HR
SEED TANK (CAPACITY)	2800 KG	MINIMUM REQUIRED POWER	130 HP



# ÖZKAN® TARIM MAKİNE



Interchangeable screens (Sieves No. 1 and No. 2) for product variation, easy deformation correction, and maintenance.




The seed conveying unit (elevator) ensures smooth operation thanks to its specially designed rubber-paddled impact system.



Wheeled stand that ensures the studded drum moves independently according to ground conditions, directing pumpkins into the drum on rough terrain.




The machine's safety system that prevents foreign objects from jamming in the cutter chamber with a friction-clutch cutter.



Flaring auger located above the seed tank ensures the seeds can flow completely into the tank.



Offers a long-lasting and easy chain tensioning option thanks to its gear, bearing, and helical spring adjustment system.



Cleaning augers carry the pumpkin and similar products, separating them from soil, mud, and grass, to the crushing chamber.



20-liter soapy washing tank.



Wheeled stand that allows the pumpkin collection drum to move independently according to rough terrain conditions.



Piston-operated stand that allows height adjustment of the tractor and the machine.



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN® TARIM MAKİNE

## B2-PLUS PUMPKIN HARVESTER MACHINE

### KHM B2 PLUS




PRODUCT CODE	KHM-B2 PLUS	SEED TANK (CAPACITY)	1100 KG
LENGTH	4300 MM	WATER TANK (CAPACITY)	450 LT
WIDTH	2400 MM	P.T.O. SHAFT SPEED	540 MIN
HEIGHT	2700 MM	WORKING CAPACITY	4 KM / HR
WEIGHT	3300 KG	MINIMUM REQUIRED POWER	100 HP / 75 KW



# ÖZKAN® TARIM MAKİNE



Interchangeable screens (Sieves No. 1 and No. 2) for product variation, easy deformation correction, and maintenance.




The seed conveying unit (elevator) ensures smooth operation thanks to its specially designed rubber-paddled impact system.



Wheeled stand that ensures the studded drum moves independently according to ground conditions, directing pumpkins into the drum on rough terrain.



The machine's safety system that prevents foreign objects from jamming in the cutter chamber with a friction-clutch cutter.



Flaring auger located above the seed tank ensures the seeds can flow completely into the tank.



Offers a long-lasting and easy chain tensioning option thanks to its gear, bearing, and helical spring adjustment system.



Cleaning augers carry the pumpkin and similar products, separating them from soil, mud, and grass, to the crushing chamber.



20-liter soapy washing tank.



Wheeled stand that allows the pumpkin collection drum to move independently according to rough terrain conditions.



Piston-operated stand that allows height adjustment of the tractor and the machine.



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN® TARIM MAKİNE

## B2 - PUMPKIN HARVESTER MACHINE


KHM B2



PRODUCT CODE	KHM B2	WATER TANK (CAPACITY)	450 LT
LENGTH	4500 MM	P.T.O. SHAFT SPEED	540 MIN
WIDTH	2300 MM	WORKING CAPACITY	4 KM / HR
HEIGHT	2700 MM	MINIMUM REQUIRED POWER	100 HP / 75 KW
WEIGHT	3000 KG	WHEEL	400 / 60 / 15.3
SEED TANK (CAPACITY)	1100 KG		



# ÖZKAN® TARIM MAKİNE



Interchangeable screens (Sieves No. 1 and No. 2) for product variation, easy deformation correction, and maintenance.



The seed conveying unit (elevator) ensures smooth operation thanks to its specially designed rubber-paddled impact system.



Wheeled stand that ensures the studded drum moves independently according to ground conditions, directing pumpkins into the drum on rough terrain.




The machine's safety system that prevents foreign objects from jamming in the cutter chamber with a friction-clutch cutter.



The weed cleaning star assembly located above the studded drum cleans grass and similar materials coming in with the pumpkins and transfers them to the second cleaning and conveying augers.



Offers a long-lasting and easy chain tensioning option thanks to its gear, bearing, and helical spring adjustment system.



Cleaning augers carry the pumpkin and similar products, separating them from soil, mud, and grass, to the crushing chamber.



20-liter soapy washing tank.



Wheeled stand that allows the pumpkin collection drum to move independently according to rough terrain conditions.



Piston-operated stand that allows height adjustment of the tractor and the machine.



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN® TARIM MAKİNE

## B1 - PUMPKIN HARVESTER MACHINE

KHM B1



PRODUCT CODE	KHM B1	SEED TANK (CAPACITY)	600 KG
LENGTH	3900 MM	WATER TANK (CAPACITY)	400 LT
WIDTH	2300 MM	P.T.O. SHAFT SPEED	540 DK / MIN
HEIGHT	2600 MM	WORKING CAPACITY	2 KM / HR
WEIGHT	2400 KG	REQUIRED POWER	60 HP / 45 KW
		WHEEL	10.0 / 75 - 15.3



# ÖZKAN® TARIM MAKİNE



The weed cleaning star assembly located above the studded drum cleans grass and similar materials coming in with the pumpkins and transfers them to the second cleaning and conveying augers.



Cleaning augers carry the pumpkin and similar products, separating them from soil, mud, and grass, to the crushing chamber.



Wheeled stand that ensures the studded drum moves independently according to ground conditions, directing pumpkins into the drum on rough terrain.



The machine's safety system that prevents foreign objects from jamming in the cutter chamber with a friction-clutch cutter.



20-liter soapy washing tank.



Offers a long-lasting and easy chain tensioning option thanks to its gear, bearing, and helical spring adjustment system.



Wheeled stand that allows the pumpkin collection drum to move independently according to rough terrain conditions.



The seed conveying unit (elevator) ensures smooth operation thanks to its specially designed rubber-paddled impact system.



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN® TARIM MAKİNE

## PUMPKIN MACHINE WITH STORAGE

DKM



PRODUCT CODE	DKM	SEED TANK	600 MM
LENGTH	3700 MM	WATER TANK	450 LT
WIDTH	1900 MM	P.T.O. SHAFT SPEED	540 MIN
HEIGHT	2600 MM	WORKING CAPACITY	20000 KG / HR
WEIGHT	1450 KG	MINIMUM REQUIRED POWER	70 HP
		WHEEL	10.0 / 75 - 15.3



# ÖZKAN® TARIM MAKİNE



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN<sup>®</sup> TARIM MAKİNE

## PUMPKIN MACHINE WITH WASHER

YKM



PRODUCT CODE	YKM	SEED TANK	50 KG BAG
LENGTH	3700 MM	WATER TANK	500 LT
WIDTH	1900 MM	P.T.O. SHAFT SPEED	540 DK / MIN
HEIGHT	1400 MM	WORKING CAPACITY	30000 KG / HR
WEIGHT	1150 KG	REQUIRED POWER	50 HP / 40 KW
		WHEEL	10.0 / 75 - 15.3



# ÖZKAN® TARIM MAKİNE



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN<sup>®</sup> TARIM MAKİNE

## PUMPKIN ROW MAKING MACHINE

KSYM



PRODUCT CODE	KSYM	OPERATING METHOD	P.T.O.
LENGTH	1700 MM	WORKING WIDTH	3500 MM
WIDTH	3000 MM	WORKING CAPACITY	12000 M <sup>2</sup> / hr
HEIGHT	1400 MM	MINIMUM REQUIRED POWER	40 HP / 25 KW
WEIGHT	700 KG		



# ÖZKAN® TARIM MAKİNE



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr





# ÖZKAN® TARIM MAKİNE

## DURABLE TRAILERS



25 TON POOL TYPE  
TRAILER

OZK-H25

10 TON POOL TYPE  
TRAILER

OZK-H10



6 TON POOL TYPE  
TRAILER

OZK-H6



REAR TIPPING  
TANDEM TRAILER

OZK-TAR





# ÖZKAN® TARIM MAKİNE

OZK - 2 TR



2-WHEEL & 4-WHEEL REAR  
TIPPING TRAILER



OZK - 4 TR

WATER PIPE TRAILER

BR



12 TON SOLID MANURE  
SPREADER TRAILER

12 KGR

10 TON SOLID MANURE  
SPREADER TRAILER

10 KGR



## Factory

Sindekhöyük Camiikebir Mah.  
İdris Aşık Cad. No : 208  
Develi/Kayseri/TÜRKİYE



## Telephone

+90 (352) 625 57 23  
+90 (536) 449 01 12



## E-Mail

info@ozkantarim.com.tr  
osman@ozkantarim.com.tr

